



## Poultry and Livestock Fabrics

### FABTEX 50

#### Product Data Sheet

PROPERTY	TEST METHOD	Typical
<b>Weight</b>	ASTM D5261	5.2 oz
<b>Material</b>		Woven Polypropylene
<b>Color</b>	Visual	Amber
<b>Construction</b>	ASTM D3775	34 x 17
<b>Thickness</b>	ASTM D1777	16 Mils
<b>Grab Tensile</b>	ASTM D4632	400 x 175 lbs
<b>Trapezoid Tear Strength</b>	ASTM D4533	150 x 60 lbs
<b>Mullen Burst</b>	ASTM D3786	325 PSI
<b>Shade</b>	ASTM D6567	35%
<b>Air Flow</b>	ASTM D737	35 CFM

- This curtain has a breathable construction to eliminate problems associated with high humidity by allowing air flow.
- It resists moisture and performs well in all climate conditions.
- This curtain will outlast anything on the market.
- Manufactured in the U.S.A.

Seller makes no warranty, express or implied, concerning the product furnished hereunder other than at the time of delivery it shall be of the quality and specifications stated herein. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. Any recommendations made by the Seller concerning uses or applications of said product are believed reliable and Seller makes no warranty of results to be obtained. This data sheet supersedes all previous data sheets for this style and is subject to change without notice. The effective date for this product data is 1/3/2020.

**Fabtex Solutions**  
**Technical Department**  
 2556 Piney Road • Morganton, NC • 28655  
 Telephone • 828 584 1240 Fax • 828 584 0880