



Poultry and Livestock Fabrics

FABTEX 160RS (Rip Stop)

Product Data Sheet

PROPERTY	TEST METHOD	Typical
Weight	ASTM D5261	16 oz.
Material		PVC
Thickness		20 mils
Color	Visual	Super Clear
Grab Tensile	ASTM D4632	300 x 280 lbs
Hydrostatic Resistance		370 psi
Cold Crack		-40 F

This curtain is one of the heaviest Rip Stop fabrics in the market. This product is a poly-vinyl coated curtain that offers great flexibility and abrasion resistance. The weave pattern includes addition strength to prevent holes from increasing in size. The super clear coating allows the most light transmission of any high weight curtain in the market. Antimicrobial added to reduce mildew.

Seller makes no warranty, express or implied, concerning the product furnished hereunder other than at the time of delivery it shall be of the quality and specifications stated herein. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. Any recommendations made by the Seller concerning uses or applications of said product are believed reliable and Seller makes no warranty of results to be obtained. This data sheet supersedes all previous data sheets for this style and is subject to change without notice. The effective date for this product data is 6/3/2022.

Fabtex Solutions
Technical Department
2556 Piney Road • Morganton, NC • 28655
Telephone • 828 584 1240 Fax • 828 584 0880