



## Poultry and Livestock Fabrics

### FABTEX 170

#### Product Data Sheet

PROPERTY	TEST METHOD	Typical
<b>Weight</b>	ASTM D5261	17 oz.
<b>Material</b>		PVC
<b>Thickness</b>		20 mils
<b>Color</b>	Visual	Super Clear
<b>Construction</b>	ASTM D3775	1000 x 1000 denier
<b>Grab Tensile</b>	ASTM D4632	300 x 280 lbs
<b>Trapezoid Tear Strength</b>	ASTM D4533	75 x 70 lbs
<b>Hydrostatic Resistance</b>		370 psi
<b>Cold Crack</b>		-40 F

This curtain is one of the heaviest and most durable curtains in the market. This product is a poly-vinyl coated curtain that offers great flexibility and abrasion resistance. The super clear coating allows the most light transmission of any high weight curtain in the market. Antimicrobial added to reduce mildew.

Seller makes no warranty, express or implied, concerning the product furnished hereunder other than at the time of delivery it shall be of the quality and specifications stated herein. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. Any recommendations made by the Seller concerning uses or applications of said product are believed reliable and Seller makes no warranty of results to be obtained. This data sheet supersedes all previous data sheets for this style and is subject to change without notice. The effective date for this product data is 12/15/15.

**Fabtex Solutions**  
**Technical Department**  
 2556 Piney Road • Morganton, NC • 28655  
 Telephone • 828 584 1240 Fax • 828 584 0880